COMG® Steel Plates

PRODUCT DATA SPECIFICATIONS

PRODUCT DESCRIPTION

OMG Steel Plates are made of Galvalume® coated steel. The round design provides an even distribution of loads and eliminates sharp corners that can damage the insulation or membrane. OMG 2-in. (50 mm) plates are used for lap seam fastening. OMG 3-in. (75 mm) plates are for fastening insulation. These plates are designed to be used with OMG fasteners.

APPLICATION

2-in. (50 mm) Metal Seam Plate: Used for attaching single-ply membrane to the substrate. Use with OMG Standard, Heavy Duty or CD-10 fasteners.

3-in. (75 mm) Ribbed Galvalume Plate: Used for attaching insulation to the substrate. Use with OMG Standard, Heavy Duty, XHD or CD-10 fasteners.

3-in. (75 mm) Galvalume Steel Plate (Flat): Used to attach insulation to the substrate. Use with OMG Standard, Heavy Duty, XHD or CD-10 fastener.

COATING

OMG steel plates are coated with AZ55 corrosion resistant coating which passes the corrosion requirements of FM Approval Standard 4470 and EAD030351-00-0402.

APPROVALS

Check with roofing system manufacturer for FM and Miami-Dade approvals for specific plates.





Factory Mutual listings refer to these products as 2-in. Metal Seam Plate, 3-in. Ribbed Galvalume Plate and OMG 3" Galvalume Steel Plate.







3-in. (75 mm) Ribbed Galvalume Plate

3-in. (75 mm) Galvalume **Steel Plate** (Flat)



PHYSICAL DATA* & ORDERING INFORMATION

PRODUCT	CAT. NO.	SIZE IN (MM)	PKG QTY	WEIGHT LBS (KG)
2" (50 mm) Metal Seam Plate	SPGA2	2 (50)	1000	29 (13.16)
3" (75 mm) Ribbed Galvalume Plate	SPGA3-RB	3 (75)	1000	38 (17.29)
3" (75 mm) Galvalume Steel Plate (Flat)	SPGA3C	3 (75)	1000	41 (18.61)

^{*}All sizes are nominal



Superior productivity. Superior performance.







